



C820G

8MP/Color/Diagnostic



8MP Color Diagnostic Monitor

DICOM	Dual-Screen	XFV	SmorTouch
QA	Ambient Light	8MP	14-bit LUT

This product has extreme high resolution, high brightness, and great color accuracy. With the build-in sensor, together with self-developed Jusha Qualitas QA software, a long-term image quality is guaranteed. It is suitable for extreme medical diagnosis, such as Mammography, DR, CR.

Jusha medical display serves over 2 billion patients



Product Features

1.DICOM Calibration

Complying with DICOM 3.14 standard and equipped with dynamic LUT, the monitor is ensured to meet the DICOM error requirements at any brightness, contrast and color temperature, improving the accuracy and stability of lesion diagnosis.

2.Integrated Front Sensor

The user can customize the black point brightness, white point brightness and environmental brightness of the DICOM curve according to the actual environment and diagnostic requirements. Build-in sensors measure the current display brightness in real time, enabling the monitor automatically adjusted to the best status, and complying with DICOM standard at any time.

3. Jusha Qualitas QA Compatible

Users can check and calibrate the monitor status by themselves, removing the side effects from panel's aging, which prolongs the lifespan of the monitor and achieving more accurate image.

4. Independent Dual Input Setup

You can change the image setting of different video source independently, such as calibration mode, resolution, color depth. Different image mode meeting various requirement.

5. Ambient Light Adaptive and Compensation

The monitor measures the ambient light in real time, and adjusts the display accordingly to ensure accurate diagnosis.

6. SmartTouch

Medical image diagnosis usually requires high brightness, and long-term use of high-brightness displays will damage your eyesight. In order to solve this problem, we provide a one-key brightening function. You can use a simple shortcut key to switch the display brightness between normal and maximum, providing great convenience for your work.

7. X-ray Film View (XFV)

The XFV can increase the brightness of the monitor to peak value, which can replace the traditional Lightbox for film reading and increase work efficiency.

Specification

Model No.	C820G
Type	IPS
Backlight	LED
Size	31.5"
Active Display	697.31(H)×392.23(V)mm
Resolution	3840×2160 (8MP)
Aspect ratio	16:9
Pixel Pitch	0.18159×0.18159mm
Response Time (Ton + Toff)	14ms
Max Calibrated Brightness	400cd/m²
Contrast Ratio	1300:1
Color Depth	10 bit
LUT	14 bit
Viewing angle	>178° (CR>10)
Sensors	Backlight Front Ambient Light Temperature Sensor
Input	DVI-D: 3840×2160@30Hz (8bit) DP1:3840×2160@50Hz (10bit) DP2:3840×2160@60Hz (10bit)
Qualitas QA Software	
Power Requirements	24VDC-3.5A
Max Power Consumption	80W
Typical Power Consumption	50W
Dimensions (With Stand)	731.4mm*538.9mm*262mm
Dimensions (Without Stand)	731.4mm*454.2mm*65.7
Net Weight (With Stand)	15.6 kg
Net Weight (Without Stand)	11.4 kg
VESA Spacing	100*100mm



EVVOTA BİYOMEDİKAL MÜHENDİSLİK
TÜRKİYE YETKİLİ DİSTRİBÜTÖRÜ
Güzelyurt Mah. Ertuğrulgazi Cad. Gökdemir Plaza
No:61D Esenyurt İstanbul 34515
0212.4382046 - evvota@evvota.com.tr



Jusha medical display serves over 2 billion patients

EVVOTA BİYOMEDİKAL MÜHENDİSLİK

📍 GÜZELYURT MAH ERTUGRULGAZI CAD. NO:61D
ESEN YURT ISTANBUL 34515

+90.212.438.2047
evvota@evvota.com.tr